semo Documentation

Release 0.1

se,mo

Aug 26, 2019

Contents

1 Discussions **3**
1.1 original intention 3

2 middlewares in blog **7**
2.1 blog.middleware 7

Python Module Index **9**

Index **11**

This is semo.

CHAPTER 1

Discussions

UI . . .

1.1 original intention

2017-2-4 by cosven.

1.1.1

1.1.2

Github Pages? wordpress?

1. Github Pages
    - . . .
    - -> push ->
2. wordpress
3. . . .
4. . . .

1.1.3

...

java
nodejs ...
php
python flask django

...

```
A:  material design
B:  ``materializecss``  ``material-design-lite``
A:  Bootstrap
B:
A:  hexo
B: Github Pages
A:  next
B:
A:  swig
B: ...
A: Swig is an awesome, Django/Jinja-like template engine for node.js.
B: django/jinja-like ?
```

django + next

mysql vs postgres vs mongodb mysql

nginx + supervisor + gunicorn ?

nginx + gunicorn + django + mysql + hexo-theme-next

1. hexo-theme-next
2.
3. duoshuo, disqus js

markdown

1.1.4

a.com a b.com b

blog.a.com/blog.b.com, happy.a.com/life.b.com


yannnli.me, cosven.me, *.*.*
NGINX
supervisor
管理服务进程
gunicorn
django + next 模板
缓存
提供图片存储
mysql
Redis 后期考虑到性能或者一些缓存功能，很可能会用到
一年活动可视化？特征提取啥的？
图片服务（或许可以使用 qiniu 等）
数据备份

CHAPTER 2

middlewares in blog

2.1 blog.middleware

middlewares for blog app.

class `blog.middleware.`**`SetBloggerByHostMiddleware`**(*get_response*)

automatic set request `blogger` property according to request Host.

for example:

if the Host request-header field is _cosven.me_, then the middle set `request.blogger` to 'cosven' according to a BloggerHostMap.

a BloggerHostMap is predefined in `blog.consts`.

Python Module Index

b

blog.middleware, 7

Index

B

`blog.middleware` (*module*), 7

S

`SetBloggerByHostMiddleware` (*class in blog.middleware*), 7